

Wayfinding Signage & Blueprint Reproductions


Photo Quality
VIP Recognition

Certification
Plaques

THE TECHNOLOGY:

ANODIZED LAYER

The glass-clear, sapphire-hard anodized layer resists chemicals, paint, abrasion and dirt.



SEALED IMAGE

The image is absorbed into the pores.

ALUMINUM LAYER

The rigid aluminum base won't peel, crack or delaminate.

BEAUTIFUL. DURABLE. SUSTAINABLE.

Since 1958, architects and designers have specified Metalphoto for high-value outdoor and indoor signage projects such as wayfinding signs, blueprint reproductions, building certification plaques and donor recognition plates.

Metalphoto photosensitive anodized aluminum allows you to capture rich, photographic quality images inside of metal – providing unmatched longevity and the durable, modern look of anodized aluminum. Because Metalphoto is a photographic process, its image resolution, clarity and durability are superior to printed or etched signs. The Metalphoto image is cleanable, graffiti-proof and impervious to sunlight and abrasion.

Metalphoto is designed for permanency – it will not fade or need to be replaced. If replacement is desired, Metalphoto is 100% recyclable.

Metalphoto of Cincinnati has been a leading full-service manufacturer of durable custom identification products for more than 50 years. Contact MPC for the best solution to your product identification needs.

PRODUCT BENEFITS

EXCEPTIONALLY DURABLE:

- + UV-stable image is permanently sealed within the anodized aluminum.
- + Virtually impervious to chemicals, heat, abrasion, salt spray and sunlight.
- + Certified for 20 year plus outdoor applications.
- + Earned more top scores than any other IUID barcode label material tested by the U.S. Navy (NSWC, Corona Division, IUID Center; August 2011).

WIDELY SPECIFIED:

- + Meets a wide array of commercial, government and military specifications.
- + Notable certifications include: MIL-STD-130N, STANAG 2290, GGP-455B(3) Type I, MIL-DTL-15024F, MIL-P-19834B and A-A-50271 (several others listed on metalphoto.com).

PHOTOGRAPHIC RESOLUTION:

- + Photographic image affords extreme detail and contrast at any size.



UV STABLE



ABRASION
RESISTANT



TEMPERATURE
RESISTANT



FLUID
RESISTANT



RECYCLABLE

PERFORMANCE CHARACTERISTICS

Because of its ability to perform across a range of challenging environments, Metalphoto meets an array of government, industrial and military specifications. Visit www.metalphoto.com for a list of specifications for which Metalphoto is qualified.

| CHARACTERISTIC | RESULT |
|---|---|
| Abrasion Resistance | No pronounced image loss, degradation or reduced readability after 7,000 cycles on an abrading wheel. |
| Acid Corrosion | No deterioration or image degradation after 24 hours in 3% nitric acid. |
| Heat Resistance | No legibility loss or degradation when subjected to 1,000°F. |
| Salt Spray Corrosion | No deleterious effect after a 720-hr salt spray (fog) test. 2.6 "Very Good" corrosion resistance after 113 days seawater exposure. |
| Accelerated Light and Weather Resistance | No pronounced deterioration of legibility after 400-hr carbon arc weatherometer exposure. (~ 20+ year outdoor life) |
| Accelerated Oxygen Aging | No discoloration or fading after 96-hr/300 psi/ 70°C oxygen bomb aging |
| Stain Resistance | No black fading when plates are exposed to tincture of iodine. |
| Cleaning Resistance | No deleterious effects when tested with alkaline cleaners (MILC- 87937 or equivalent) for aircraft surfaces. |
| Low Temperature Resistance | No deleterious effect or image fade after 1 hour at -50°F. No impairment of legibility upon exposure at -67°F. |
| Organic Solvent Resistance | No softening, staining or noticeable fade after 24-hr exposure to: JP-4 fuel, Gasoline, Mineral Spirits, Methyl Ethyl Ketone, Turpentine, Turbine & Jet Fuel, Kerosene, Xylo, Acetone, Toluol, Heptane, Trichlorethylene, MIL-H-5606 Hydraulic Fluid and MIL-L-7808 Jet Engine Oil. |
| Fungus Resistance | Visual reading of "0" per ASTM-G21. |
| Thermal Shock | No deterioration after 3 cycles between -65°C and 125°C |
| Moisture Resistance | No deterioration after 10 humidity cycles per MIL-STD-202, method 106. |

TECHNICAL SPECIFICATIONS

MATERIAL: Anodized Aluminum

SIZES: Up to 24" x 40"

THICKNESSES: .003", .005", .008", .012", .020", .032", .039", .063", .090", .125"

FINISHES:



MATTE
non-reflective
with dull finish



SATIN
semi-gloss medium
reflective material



4
brushed to resemble
a stainless steel finish



GLOSS
highly reflective,
mirror-like

CONTACT MPC

Call **1-800-528-4058** or visit our website at **MPofCinci.com**

*Metalphoto of Cincinnati does not warrant the performance of its materials in any environment.
Metalphoto is a registered trademark of Horizons Incorporated.

Ver. 1.2 JULY 2013



Metalphoto of Cincinnati

1080 Skillman Drive
Cincinnati, OH 45215

T: 1-800-528-4058
F: 513-772-8306

E: cincics@mpofcinci.com
www.mpofcinci.com